



LUBEGARD® *for* **V-TWIN'S**  
Transmission Protectant

- BENEFITS**
- Suitable for use in all 4 and 5 speed FL, FLT, FX, FXD and FXR Transmissions or any separate sump transmission applications.
  - Exclusive LXE® Technology for enhanced heat reduction and extended transmission fluid life.
  - Improves shift quality.
  - Reduces drive train power loss.
  - Reduces wear on gears and bearings.
  - Increases heat transfer from inside case through unit case wall.

#40602

**DIRECTIONS:**

Add contents of bottle directly to transmission. (4 oz. per Quart of Transmission Fluid)



LUBEGARD® *for* **V-TWIN'S**  
Engine Oil Protectant

- BENEFITS**
- Suitable for use in all '84 and later FL, FLT, FX, FXD, FXR, and FXST engines or any 4 cycle V-Twin engine application with separate oil sump.
  - For use with conventional or synthetic motorcycle engine oil.
  - Exclusive LXE® Technology for enhanced heat reduction and extended life for the engine.
  - Increases heat transfer from inside engine case through engine case wall for reduced engine temperatures.
  - Reduces wear on all metal surfaces. Eliminates wear from cold start up.
  - Better fuel mileage with extended oil life.
  - Contains no harmful additives such as chlorinated hydrocarbons or solid lubricants like Teflon or graphite.

#40910

**DIRECTIONS:** Add contents of bottle directly to engine. Bottle will treat 3-4 Quart capacity sump. (3 oz. per Quart of engine oil)



LUBEGARD® *for* **V-TWIN'S**  
Primary Case Chain Protectant

- BENEFITS**
- Suitable for use in '84 and later FL, FLT, FX, FXD, FXR and FXST Models with Wet Type diaphragm Spring Clutch.
  - For use with conventional or synthetic motorcycle primary chain case fluid.
  - Exclusive LXE® Technology for enhanced heat reduction, reduced wear and extended life for the primary chain.
  - Formulated to prevent clutch chatter, shudder and slippage while maintaining the proper coefficient of friction for long life and proper clutch operation.
  - Improves shift quality.
  - Increases heat transfer from inside primary case through primary unit case wall.

#40104

**DIRECTIONS:**

Add contents of bottle directly to primary case. (4 oz. per Quart of Primary Fluid)



LUBEGARD® *for* **Water-Cooled  
Motorcycles & ATV's**  
Coolant Treatment

- BENEFITS**
- Protects aluminum from electrolysis
  - Reduces operating temperatures
  - Provides 5 year corrosion protection
  - Prevents hard-water scales and deposits

**DIRECTIONS:**

Directions: With engine cool, pour into radiator, start engine and run 10 min. Always maintain a minimum of 15% antifreeze in street-driven motorcycles. Ratio: 1 bottle treats systems 2-6 qrts in capacity. Frequency: Add 1 bottle every year or 30,000 miles. After 5th consecutive year, drain, flush, and refill cooling system.

#40820

**AVAILABILITY:**

Stock No.	Unit Size	Case Weight/QNTY
40602	4 oz.	3.75 lbs. (12/c)
40910	10 oz.	8.78 lbs. (12/c)
40104	4 oz.	3.75 lbs. (12/c)
40820	4 oz.	3.75 lbs. (12/c)

